

DSP-6LP Vehicle Detector

Ultra Low Power Solar Friendly Plug and Play "Micro" Detector

OPERATION

The DSP-6LP vehicle detector is designed for solar powered gate applications. This detector will operate on any voltage from **10 to 30 Volts AC or DC** and draws approximately 1 milliampere while waiting for a car. The power LED winks continuously once per second to indicate the detector is operating in the low power mode. The DSP-6LP detector beats all competition for reliability, simplicity, and "no car" current consumption.

This series of Diablo's detectors are covered by United States patent number US 7,132,959 "Non-Interfering Vehicle Detection". These detectors are virtually cross-talk free in most applications.

Working on battery-powered and other parking and access control loop applications, the DSP-6LP is preset to the normal sensitivity level used in parking/access control applications, and tunes itself to the best operating frequency.

This micro-sized detector will automatically adjust its sensitivity level when used on different sized loops. Environmental conditions are constantly compensated with the DSP-6LP's *HYPERTRACK* software.

FEATURES

Loop Size - Works on any in-ground inductive loop from 20 to 1200 μ H.

Indicators - Separate Power and Detect LED's. The green Power LED will wink continuously once per second under normal operation. The red Detect LED will turn on solid for a vehicle.

Sensitivity - Automatic - compensates for large loops and large lead-ins.

Loop Failure - The green power indicator flashes twice per second if the loop circuit is open and 10 times per second if the loop circuit is shorted. This detector operates in the fail secure mode and will not output a "Detect" for either of these loop failure conditions. **This "Fail secure" detector should be used on "free exit" loops.**



Power - 10 to 30 Volts AC or DC. Approximately 1 mA (no car and all loop sizes) and less than 25 mA with a car on the loop.

Size - Height: 1.52" Width: 2.9" Depth: 1.56"

Connector - Removable 7-pin terminal block. Pin assignments are shown below - from left to right:

- 1 - Relay (NC) (opens for detect) 1amp max
- 2 - Relay Common
- 3 - Relay (NO) (closes for detect) 1amp max
- 4 - Power Common
- 5 - Power in (10 to 30 Volts AC or +DC)
- 6 - Loop
- 7 - Loop

Operating Temperature -35°F to 165°F (-37°C to 74°C)



Stuck in traffic for over 30 years!

Phone: (866) 395-6677 (Toll Free)

Web Site: www.diablocontrols.com

DSP6LP_CUT_E