



# PROFESSIONAL ACCESS CONTROLS

## DRIVEWAY WAND SENSOR

*Automatically activates gate operators "Hands-Free" when a vehicle approaches. Designed for residential, agricultural, and commercial applications.*

*Easy to install. Avoid the headaches associated with installing exit and entry loop detector systems, installs in 1/3 the time.*



### Driveway Wand Sensor Direct burial wire lengths:

- (FM139) 50 ft. (15.3 m)
- (FM140) 100 ft. (30.5 m)
- (FM141) 150 ft. (45.7 m)
- (FM141-250) 250 ft. (76.2 m)
- (FM141-500) 500 ft. (152.4 m)
- (FM141-1000) 1000 ft. (304.8 m)

## STANDARD FEATURES

- Electromagnetic sensor detects vehicles-in-motion.
- Relay latch time of 2 seconds.
- Compatible with all automatic gate operators, or other systems requiring a dry contact input device.
- Potentiometer board adjusts sensitivity from 3 to 12 foot radius to accommodate many applications and situations.
- Ideal for solar application, 1.5 mA current consumption.
- Wide input voltage range (8-32 vAC or 8-26 vDC).
- Designed to reject line noise of 50Hz or 60Hz; improves detection capability near power lines and avoids crosstalk frequency issues.
- Dimensions: 1.75" (44.5 mm) diameter x 16.75" (425.4mm) long.
- May not be used as a safety device.
- No drive over loads to get damaged or fail, common with loop detector systems.

## AVAILABLE FROM:



**Driveway Wand Sensor  
Control Board**



1-800-543-GATE (4283) • [www.gtopro.com](http://www.gtopro.com)

GTO®, GTO/PRO®, Bulldog®, are registered trademarks of GTO, Inc. Professional Access Systems™, is a trademark of GTO, Inc. and are the exclusive property of GTO, Inc. ("GTO"). All rights are reserved by GTO, and these marks may not be used, in any for without the prior, written permission of GTO. Copyright 2007 rev-02-2007